



	<table><tr><td>L</td><td>1778 mm</td></tr><tr><td>A</td><td>62 mm</td></tr><tr><td>H</td><td>38 mm</td></tr></table>	L	1778 mm	A	62 mm	H	38 mm
L	1778 mm						
A	62 mm						
H	38 mm						

Wired supporting structure for continuous channels, suitable for: lighting units 3F Linux L, 3F Linux D, 3F Linux DR, other luminaires or transport of electrical lines.

MECHANICAL

Wired base in hot galvanised steel and painted with polyester base in black colour, obtained through rolling process.
Saline-mist resistance equal to 500hrs and damp resistance equal to 700hrs.
Dimensions: 1778x62 mm, height 38 mm.
IP40 protection degree.
Glow-wire test resistance 850°C.

ELECTRICAL

5-pole through power supply line with with H07Z-U Halogen Free cables (2.5 mm² HT90 cross-section), equipped with quick connection start/end channel terminal blocks, non-reversible, 1 power supply pedestal.

INSTALLATION

Ceiling / Suspended.
All accessories dedicated to this product are available on the Catalog and on our website www.3F-Filippi.com.

APPLICATIONS

Environments: commercial, exhibition areas, transit areas, lobbies or waiting rooms, shops, schools.

WARNING

Luminaire designed for disposal/recycling at end-of-life.